



DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011

Name of the product: LIQUID RUBBER TROWELGRADE B-400

No. B-400

1. Unique identification code of the product-type:
EN 15651-4: PW-EXT-INT-CC
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
batch number: see packaging of the product
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Sealant for movement joints in floors for interior and exterior application
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
Russlar Manufacturing Inc
2140 Winston Park Drive
Oakville, Canada,
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
Jacob Karam
2140 Winston Park Drive
Oakville, Canada
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 4
(System 3 for the reaction to fire pending)
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
NA



8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not relevant

9. Declared performance

Conditioning: allow to cure until moisture content is <10%

Substrate: NA


Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	TBA	EN 15651-4:2012
Release of chemicals dangerous to the environment and health	none	EN 15651-4:2012
Water tightness and air tightness		
Tensile properties at maintained extension	TBA	EN 15651-4:2012
Loss of volume	TBA	EN 15651-4:2012
Tear resistance	Not applicable	EN 15651-4:2012
Adhesion/cohesion properties at maintained extension after 28 days water immersion	TBA	EN 15651-4:2012
Adhesion/cohesion properties at maintained extension after 28 days salt water immersion	TBA	EN 15651-4:2012
Tensile properties (i.e. at maintained extension) at -30°C	TBA	EN 15651-4:2012
Durability	TBA	EN 15651-4:2012

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Jacob Karam
CEO Russlar Manufacturing

[place, date]
(place and date of issue)


.....
(signature)

Edition: January 2013